

VIS LINE INTERACTIVE UPS SYSTEMS



Sine Wave
Independent
Voltage

Line Interactive Sine Wave UPS Systems offering maximum application compatibility



- Pure Sine Wave Output
- Microprocessor Controlled
- IEC Socket Outlets
- LCD display
- Cold Start
- Buck & Boost Automatic Voltage Regulation (AVR)
- Auto Restart
- Standby Charging
- Full Serial Communications via RS232 or USB
- RJ45 Network Protection
- Available in 1KVA & 2KVA models



VIS1000B

VIS2000B

VIS LINE INTERACTIVE UPS SYSTEMS

Sine Wave
Independent
Voltage



SPECIFICATIONS

MODEL	VIS1000B	VIS2000B
CAPACITY (VA/WATTS)	1000 / 700	2000 / 1400
INPUT		
Nominal Voltage	230VAC 50Hz	
Range (VAC)	162 - 290	
Frequency Range		
OUTPUT		
Voltage (Battery Mode)	230V ±10%	
Frequency (Battery Mode)	50Hz ±1%	
Transfer Time	10ms Maximum, typically 2-6ms	
Waveform	Sine Wave	
BATTERY		
Capacity (Qty)	12V 7Ah (x2)	12V 10Ah (x2)
Typical Recharge	6 hours to 90%	
INDICATORS		
LED	N/A	
LCD	Voltages, Load, Battery	
Alarm	Audible Alarm on UPS events.	
COMMUNICATIONS		
Interface	RS232 & USB	
Type	Serial	
Software	ViewPower	
PHYSICAL		
Environment	0-40°C. 0-90% Rel Humidity Non condensing	
Noise	<40dB	<55dB (inc fan)*
Input Connector	IEC	
Output Connectors	4xIEC	6xIEC
Dimensions (WxDxH mm)	146x350x160	146x397x205
Weight (kg)	9	14
STANDARDS		
CE	EN62040	

*Fan on VIS2000B is inactive in normal operation

Although every effort has been made to ensure the accuracy of these specifications, they are provided for guidance only and do not form part of any contract.